

EE003CA

1. Chemical Product and Company Identification

Product Name : Epoxy EE003CA		
Recommended and Restricted Uses :		
Manufacturer, importer or supplier name : Everwide Chemical Company		
Manufacturer, importer or supplier address : No. 36, Dougong 6th Rd., Douliu City, Yunlin County 64069, Taiwan		
Consultant : RD Assistant Engineer, Su-Huan, Li		
TEL: (886) 5-5574717 ext: 852 E-mail: suhane@everwide.com.tw		
Emergency Telephone : (886) 5-5574717	FAX : (886) 5-5574719	

2. Hazards Identification

Chemical Hazard Classification : Serious eye damage/eye irritation category 2B, Skin sensitizer category 1. Symbol Contents :



Symbol : Exclamation mark.

Signal word :Warning.

Hazard Statement : Causes eye irritation, May cause allergic skin reaction.

Precautionary Statement : Store in well-ventilated place. Keep away from ignition sources—No smoking. Do not wear contact lenses. Chemical safety goggles are recommended. Avoid eyes and skin contact. Wear suitable protective equipment. Call a doctor or physician if you feel unwell.

Other Effects : -----

3. Ingredients

Hazardous ingredient name	Concentration WT%	CAS No.		
Epoxy resin1	77	25085-99-8		
Epoxy resin2	23	Not assigned		

4. First Aid Measures

The First-aid Measures for Different Exposure Routes :

Inhalation : Remove to fresh air. If symptoms persist, obtain medical attention.

Skin Contact : Immediately wash with soap and water. Wash contaminated clothing before reuse. Get medical attention if symptoms occur.

Eye Contact : Flush with lukewarm water at least 15 minutes. Seek medical advice.

Ingestion : Clean with water and drink plenty of water. Induce vomiting. Keep individual calm. Obtain medical attention.

The Most Important Symptoms and Hazardous Effects : Nausea and irritating.

The Protection of First-aides : Wear impervious gloves. Avoid contacting the pollutant.

Notes to Physicians : Do not induce vomiting. Never give anything by mouth to an unconscious person.

5. Fire-Fighting Measures

Suitable Fire Extinguishing Media : Carbon dioxide, foam or dry chemical.

Specific Hazards May Be Encountered During Fire-fighting:May cause carbon monoxide, acetone, aldehyde, ammonia and some organism materials.

Specific Fire-fighting Methods : Move to the safe area.

Special Equipment for The Protection of Firefighters : Self-contained breathing apparatus and protective clothing should be worn in fighting large fires involving chemicals

6. Accidental Release Measures

Personal Precautions : Wear suitable protective equipment. Clean the floor to prevent from slipping and falling. Environmental Precautions : Extinguish the flame. Do not flush into surface water or sanitary sewer system. Advise water authority if spillage has entered water course or drainage system.

Methods for Cleaning Up : Spontaneous hazardous polymerization may occur. Eliminate sources of ignition. Use eye and skin protection. Maintain adequate ventilation. Soak up with inert absorbent. Store in a half filled, closed container until disposal.

7. Handling and Storage

Handling :	Wear suitable protective equipment.
	Avoid leak.
	Keep away from light and heat.
	Avoid eye and skin contact.
	Keep the place ventilated.
Storage :	Keep away from flame and sunlight.
_	Keep in a cool, well ventilated area away from heat, sparks and open flame.
	Keep container tightly sealed.

8. Exposure Controls/Personal Protection

Engineering Controls : If handling results in aerosol or vapor generation, local exhaust ventilation is recommended. Do not smoke and eat in the work area. Keep the workplace clean.

	limits (TWA/8hr)			
	average exposure	limits (STEL)	limits (CEILING)	(BEIs)
Ingredients	Time weighted	Short-term exposure	Maximum exposure	Biological Standards
Control Parameters				

Personal Protection :

Respiratory : Respiratory equipment and gas mask.

Hand protection : Use protective gloves.

Eyes : Do not wear contact lenses. Chemical safety goggles are recommended.

Skin : Avoid skin contact. Use impermeable gloves and protective clothing as necessary to prevent skin contact. Wash contaminated clothing before reuse.

Other Hygienic Practices : Use good personal hygiene practices. Wash hands and face before eating and drinking. Exercise more to keep healthy. Ingest food which contains vitamins and minerals. Do physical examination regularly.

9. Physical and Chemical Properties

Odor : Mild
Melting Point:°C
Boiling Point :ºC
Flash Point:>250 ºC
Test Method : Closed-cup
Explosion Limits :
Upper(UEL) : ; Lower(LEL) :
Vapor Density: (Air=1)
Solubility in Water :
Evaporation Rate :

10. Stability and Reactivity

Stability	Stable.
Hazardous	May occur.
Polymerization	
Incompatibility	Avoid flammable, ignitable, heat source, spark, flame, strong oxidant, free radical initiator, peroxide and basic materials.
Hazardous Decomposition Products	Carbon monoxide, acetone, aldehyde, ammonia.

11. Toxicological Information

Acute Toxicity : Inhalation : May irritate to nose and throat.

Skin:Irritating to skin if contact. Eye:The vapor may Irritate to eye.

Eye · The vapor may initate to eye.

Ingestion · May cause neadache, nausea, dizziness and tiredness.				
Ingredients	Concentration %	LD ₅₀ (Lethal Dose 50)	LC ₅₀ (Lethal Concentration 50)	
Epoxy resin1	77			
Epoxy resin2	23			
Local Effects :				
Sensitization :				
Chronic Toxicity or Long Term Toxicity :				
Specific Effects :				

12. Ecological Information

Ecotoxicity:	
Persistence / Degra	adability:
Bioaccumulation :	
Mobility:	
Other Information :	Avoid the products enter into drainage or soli surface. After the product curing, it can be
disposed by followi	ng local regulations.

13. Disposal Considerations

Recommended methods of Disposal : Recover or recycle if possible. Otherwise, incineration following local regulations.

14. Transport Information

Jnited Nation Number (UN No.):
Proper Shipping Name:
Class :
Packing Group :
Marine pollutant (Yes/No):No
Special delivery methods and precautions:
ATA-DGR : Not Restricted AS DGR 63rd edition

15. Regulatory Information

Traffic Regulation

Occupational Safety and Health Act

Regulation of Labelling and Hazard Communication of Dangerous and Harmful Materials Standards of Permissible Exposure Limits of Airborne Hazardous Substances in Workplace Management Regulations for the Import, Export, Transit and Transshipment of Waste

Public Hazardous Materials and Flammable Pressurized Gases Establishment Standards and Safety Control


Procedures

16. Other Information

Title	Name : Everwide Chemical Company		
	Address : No. 36, Dougong 6th Rd., Douliu City, Yunlin County 64069, Taiwan		
	Telephone : (886) 5-5574717		
Prepare By	RD Assistant Engineer, Su-Huan, Li		
Revision Date	2023-05-17		

The data contained in this bulletin is provided only as a guide for evaluation/consideration. These material characteristics are typical properties that are based on a limited number of samples tested in the laboratory. We cannot assume responsibility for results obtained by others over whose methods we have no control. It is the user's responsibility to determine suitability for the user's purpose of any product or method. We recommend that each prospective user test his proposed application before repetitive use, using this data as a guide.





EE003CB

1. Chemical Product and Company Identification

Product Name : Hardener EE003CB		
Recommended and Restricted Uses :		
Manufacturer, importer or supplier name : Everwide Chemical Company		
Manufacturer, importer or supplier address : No. 36, Dougong 6th Rd., Douliu City, Yunlin County 64069, Taiwan		
Consultant : RD Assistant Engineer, Su-Huan, Li		
TEL : (886) 5-5574717 ext : 852 E-mail : suhane@everwide.com.tw		
Emergency Telephone : (886) 5-5574717	FAX:(886) 5-5574719	

2. Hazards Identification

Chemical Hazard Classification:Serious eye damage/eye irritation category 2B, Skin sensitizer category 1. Symbol Contents:



Symbol : Exclamation mark.

Signal word:Warning.

Hazard Statement : Causes eye irritation, May cause allergic skin reaction.

Precautionary Statement : Store in well-ventilated place. Keep away from ignition sources – No smoking. Do not wear contact lenses. Chemical safety goggles are recommended. Avoid eyes and skin contact. Wear suitable protective equipment. Call a doctor or physician if you feel unwell.

Other Effects : -----

3. Ingredients

Hazardous ingredient name	Concentration WT%	CAS No.		
Polymercaptan	100	Not assigned		

4. First Aid Measures

The First-aid Measures for Different Exposure Routes :

Inhalation : Remove to fresh air. If symptoms persist, obtain medical attention.

Skin Contact : Immediately wash with soap and water. Wash contaminated clothing before reuse. Get medical attention if symptoms occur.

Eye Contact : Flush with lukewarm water at least 15 minutes. Seek medical advice.

Ingestion : Clean with water and drink plenty of water. Induce vomiting. Keep individual calm. Obtain medical attention.

The Most Important Symptoms and Hazardous Effects : Nausea and irritating.

The Protection of First-aides : Wear impervious gloves. Avoid contacting the pollutant.

Notes to Physicians : Do not induce vomiting. Never give anything by mouth to an unconscious person.

Suitable Fire Extinguishing Media : Carbon dioxide, foam or dry chemical.

Specific Hazards May Be Encountered During Fire-fighting:May cause carbon monoxide, acetone, aldehyde, ammonia and some organism materials.

Specific Fire-fighting Methods : Move to the safe area.

Special Equipment for The Protection of Firefighters : Self-contained breathing apparatus and protective clothing should be worn in fighting large fires involving chemicals

6. Accidental Release Measures

Personal Precautions : Wear suitable protective equipment. Clean the floor to prevent from slipping and falling. Environmental Precautions : Extinguish the flame. Do not flush into surface water or sanitary sewer system. Advise water authority if spillage has entered water course or drainage system.

Methods for Cleaning Up : Spontaneous hazardous polymerization may occur. Eliminate sources of ignition. Use eye and skin protection. Maintain adequate ventilation. Soak up with inert absorbent. Store in a half filled, closed container until disposal.

7. Handling and Storage

Handling :	Wear suitable protective equipment.
	Avoid leak.
	Keep away from light and heat.
	Avoid eye and skin contact.
	Keep the place ventilated.
Storage :	Keep away from flame and sunlight.
_	Keep in a cool, well ventilated area away from heat, sparks and open flame.
	Keep container tightly sealed.

8. Exposure Controls/Personal Protection

Engineering Controls : If handling results in aerosol or vapor generation, local exhaust ventilation is recommended. Do not smoke and eat in the work area. Keep the workplace clean.

	limits (TWA/8hr)			
	average exposure	limits (STEL)	limits (CEILING)	(BEIs)
Ingredients	Time weighted	Short-term exposure	Maximum exposure	Biological Standards
Control Parameters				

Personal Protection :

Respiratory : Respiratory equipment and gas mask.

Hand protection : Use protective gloves.

Eyes : Do not wear contact lenses. Chemical safety goggles are recommended.

Skin : Avoid skin contact. Use impermeable gloves and protective clothing as necessary to prevent skin contact. Wash contaminated clothing before reuse.

Other Hygienic Practices : Use good personal hygiene practices. Wash hands and face before eating and drinking. Exercise more to keep healthy. Ingest food which contains vitamins and minerals. Do physical examination regularly.

9. Physical and Chemical Properties

Odor:Mercaptan-like odor
Melting Point:ºC
Boiling Point :ºC
Flash Point : >93 °C
Test Method : Closed-cup
Explosion Limits :
Upper(UEL) : ; Lower(LEL) :
Vapor Density: (Air=1)
Solubility in Water :
Evaporation Rate :

10. Stability and Reactivity

Stability	Stable.
Hazardous	May occur.
Polymerization	
Incompatibility	Avoid flammable, ignitable, heat source, spark, flame, strong oxidant, free radical initiator,
	peroxide and basic materials.
Hazardous	Carbon monoxide, acetone, aldehyde, ammonia.
Decomposition	
Products	

11. Toxicological Information

Acute Toxicity : Inhalation : May irritate to nose and throat.

Skin:Irritating to skin if contact. Eye:The vapor may Irritate to eye.

Indestion : May cause headache, nausea, dizziness and tiredness.

ingeotion + may bado	5 1164446116, 1144564, 412		
Ingredients	Concentration %	LD ₅₀ (Lethal Dose 50)	LC ₅₀ (Lethal Concentration 50)
Polymercaptan	100		
Local Effects :			
Sensitization :			
Chronic Toxicity or Lo	ng Term Toxicity:	-	
Specific Effects :			

12. Ecological Information

Ecotoxicity:
Persistence / Degradability:
Bioaccumulation :
Mobility:
Other Information:Avoid the products enter into drainage or soli surface. After the product curing, it can be disposed by following local regulations.

13. Disposal Considerations

Recommended methods of Disposal : Recover or recycle if possible. Otherwise, incineration following local regulations.

14. Transport Information

United Nation Number (UN No.):		
Proper Shipping Name:		
Class :		
Packing Group :		
Marine pollutant (Yes/No):No		
Special delivery methods and precautions :		
IATA-DGR:Not Restricted AS DGR 63rd edition		

15. Regulatory Information

Traffic Regulation

Occupational Safety and Health Act

Regulation of Labelling and Hazard Communication of Dangerous and Harmful Materials Standards of Permissible Exposure Limits of Airborne Hazardous Substances in Workplace Management Regulations for the Import, Export, Transit and Transshipment of Waste Public Hazardous Materials and Flammable Pressurized Gases Establishment Standards and Safety Control Procedures

16. Other Information

Title	Name : Everwide Chemical Company	
	Address : No. 36, Dougong 6th Rd., Douliu City, Yunlin County 64069, Taiwan	
	Telephone : (886) 5-5574717	
Prepare By	RD Assistant Engineer, Su-Huan, Li	
Revision Date	2023-05-17	

The data contained in this bulletin is provided only as a guide for evaluation/consideration. These material characteristics are typical properties that are based on a limited number of samples tested in the laboratory. We cannot assume responsibility for results obtained by others over whose methods we have no control. It is the user's responsibility to determine suitability for the user's purpose of any product or method. We recommend that each prospective user test his proposed application before repetitive use, using this data as a guide.